

Crossply

	Tread Pattern	Inflated Diameter		Inflated Width		Loaded Static Radius		Rolling Circ. @30 MPH		Revs Per Mile @30 MPH	Max Load	Maximum Pressure		Measuring Rim Width	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.			kg.	psi	bar	in.
5.20-13	C41 T/L	22.80	579	5.51	140	10.63	270	68.50	1740	925	335	30	2.10	4.00	102
640-13	C49	25.12	638	6.38	162	11.61	295	75.12	1908	843	475	30	2.10	4.50	114
7.50-h13	Road Speed T/L	26.10	663	7.48	190	12.01	305	78.58	1996	806	510	30	2.10	5.00	127
5.20-14	D75 T/L	24.02	610	5.24	133	11.18	284	72.24	1835	877	375	30	2.10	3.50	89
5.50-15	C49 T/L	26.25	667	6.10	155	12.50	318	84.82	1994	807	350	30	2.10	4.50	114
5.90h15	Road Speed RS T/L	26.00	660	6.40	163	12.05	306	78.55	1995	807	435	30	2.10	4.50	114
6.00/6.40-15	C49	27.25	692	6.40	162	12.70	323	81.75	2076	778	530	30	2.10	4.50	114
6.40h15	Road Speed RS5	26.89	683	6.85	174	12.52	318	81.45	2069	778	530	30	2.10	4.50	114
6.70h15	Road Speed RS T/L	27.80	706	7.04	189	12.83	326	83.82	2129	756	560	30	2.10	4.50	114
8.15h15	Road Speed RS5	27.80	706	8.27	210	12.76	324	83.31	2116	760	750	36	2.50	6.00	152
8.20h15	Fort WH4	30.15	766	8.35	212	13.90	353	88.60	2250	715	775	30	2.10	6.00	152
8.90s15	Fort WH4	31.30	795	9.15	232	14.50	368	92.70	2355	684	1060	36	2.50	6.00	152
6.00h16	Road Speed RS5	27.90	709	6.90	175	13.00	330	84.65	2150	749	450	30	2.10	4.50	114
6.70h16	Road Speed RS5	28.80	732	7.40	189	13.35	339	87.00	210	728	572	30	2.10	4.50	114

Radial

	Tread Pattern	Inflated Diameter		Inflated Width		Loaded Static Radius		Rolling Circ. @30 MPH		Revs Per Mile @30 MPH	Max Load	Maximum Pressure		Measuring Rim Width	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.			kg.	psi	bar	in.
155SR15	SP4 T/L	24.80	630	6.18	15.7	11.42	290	75.67	1922	837	475	31	2.20	4.5	114

	Tread Pattern	Inflated Diameter		Inflated Width		Loaded Static Radius		Rolling Circ. @30 MPH		Revs Per Mile @30 MPH	Max Load	Maximum Pressure			Measuring Rim Width	
		in.	mm.	in.	mm.	in.	mm.	in.	mm.			kg.	psi	bar	in.	mm.
*185HR15	SP SPORT	26.54	674	7.40	188	12.20	310	80.43	2043	788	615	33	2.30	5.50	140	
ER70HR15	SP SPORT T/L	26.54	669	7.95	202	12.20	310	80.24	2038	790	650	34	2.35	5.50	140	