Tyre/Wheel Equipment and Inflation Pressures

for

Cars (1979-1983)

Published by:

DUNLOP

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
AC										
3000 ME (1979-1981)	205/60VR14		•	18	25	18	25	20	30	7J-14
3000 ME (1982-1983)	205/60VR14		•	18	25	22	29	22	30	6.5J-14
Alfa Romeo										
Alfasud 1350; 1500; 1.5TI (1979-80)	165/70SR13	•		26	20	29	33			5.5J-13
Alfasud Sprint; Sprint Veloce (1979-80)	165/70SR13	•		26	20	29	33			5.5J-13
Alfasud 1.3; 1.5 (1981-82)	165/70SR13		•	27	23	30	25			5J-13
Alfasud TI; TIS; TIS Veloce (1981-82)	165/70SR13		•	27	23	30	25			5.5J-13
Alfasud 1.3; 1.5; TI (1983)	145/SR13		•	27	21	30	26			4.5J-13
Alfasud Sprint Veloce (1981)	165/70SR13		•	27	23	27	25			5.5J-13
Alfasud Sprint Veloce (1982)	165/70SR13		•	27	21	30	24			5.5J-13
Alfasud Sprint Veloce (1983)	165/70SR13		•	26	20	29	23			5J-13
Giulietta 1.6 (1979-82)	165SR13		•	26	29	26	29			5.5J-13
	or 185/70SR13		•	26	29	26	29			5.5J-13
Guilietta 1.6 (1983)	185/70SR13		•	27	30	30	33			5.5J-13
Guilietta 1.8 (1979-80)	185/70SR13		•	26	29	26	29			5.5J-13
Guiletta 1.8 (1981-83)	185/70SR13		•	27	30	30	33			5.5J-13
Guiletta 2.0 (1981-83)	185/65HR14		•	27	30	30	33			5.5J-14
Alfetta 1.6GT (1980)	165/SR14	•		23	26	23	26			5J-14
	or 185/70SR14	•		23	26	23	26			5J-14
Alfetta 2000L (1979-80)	185/70SR14	•		26	26	26	32			5.5J-14
Alfetta 2000L (1981-83)	185/70SR14	•		27	27	30	32			5.5J-14
Alfetta GTV 2.0 (1979-80)	185/70SR14	•		24	26	24	26			5.5J-14
Alfetta GTV 2.0 (1981-82)	185/70SR14	•		25	27	25	27			5.5J-14
Alfetta GTV 2.0 (1983)	185/70SR14		•	25	27	28	30			5.5J-14
Alfa V6 (1981)	195/70HR14	•		28	29	32	33			5.5J-14
Alfa V6 (1982-83)	195/70HR14	•		27	29	30	32			5.5J-14
Alfa GTV6 (1982-83)	195/60HR15		•	29	29	32	32			6J-15
Aston Martin										
V8 Manual (1979-80)	225/70VR15		•	30	30	30	30	35	35	7L-15
V8 Manual (1981-)	225/70VR15		•	30	30	35	35	35	35	7L-15
V8 Manual (1982-83)	225/70VR15		•	30	30	45	45	45	45	7L-15
V8 Auto (1981)	235/70VR15		•	28	28	28	28	35	35	7L-15
V8 Auto (1982-83)	235/70VR15		•	30	30	40	40	40	40	7L-15
Vantage (1979-80)	225/60VR15		•	30	30	30	30	35	35	7L-15
Vantage (1981)	255/60VR15		•	30	30	35	35	35	35	7L-15
Vantage (1982-83)	255/60VR15		•	40	40	50	50	50	50	7L-15
Lagonda (1979-80)	235/70HR15		•	30	30	30	30	35	35	6J-15
Lagonda (1981-83)	235/70HR15		•	28	28	35	35	35	35	6J-15
Volante (1979-81)	225/70VR15		•	30	30	30	30	35	35	7L-15
Volante (1982-83)	235/70VR15		•	30	30	40	40	40	40	7L-15
Audi										
80L; GL; GLS; LE (1979-83)	155SR13		•	24	24	26	29			5J-13
	or 175/70SR13		•	24	24	26	29			5J-13
	or 165SR13		•	24	24	26	29			5J-13
80 GL Estate (1979-80)	175/70SR13		•	24	24	27	31			5J-13
80 GLE (1979-83)	185/60HR14		•	23	23	25	26			6J-14
Avante 100 range (1979-83)	165SR14		•	29	29	32	32			5.5J-14
	or 185/70HR14		•	27	27	31	31			5.5/6J-14
200 SE (1981-82)	205/60HR15		•	26	27	27	27			6J-15
200 (1983)	205/60HR15		•	26	24	34	31			6J-15
200 S Turbo (1981-82)	205/60HR15		•	26	27	27	27			6J-15
Quattro (1982-83)	205/60VR15		•	26	24	28	28			6/7J-15
Austin										
Allegro MkII; 1100; 1300 & MkIII (1979-83)	145SR13		•	26	24	26	24			4.00C-13
Allegro MkII; 1750; 1500 & MkIII (1979-83)	155SR13		•	26	24	26	24			4.50C-13
Allegro MkII Estate 1300 (1979-83)	145SR13		•	26	24	26	32			4.50C-13
Allegro MkII Estate 1500 & 1750 (1979-80)	155SR13		•	26	24	26	32			4.50C-13
Allegro 3 Estate 1.3 (1981-83)	145SR13		•	26	24	26	30			4.50C-13
Allegro 3 Estate 1.5; 1.7 (1981-83)	155SR13		•	26	30	26	30			4.50C-13
Allegro 3 Equipe (1981)	165/70SR13		•	26	26	26	26			3.5J-13
Maxi 1500; 1750 (1979-80)	155SR13		•	26	24	26	24			4.50C-13
	or 175/70SR13		•	26	24	26	24			4.50C/5J/5.5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Austin—cont.										
Maxi 2 (1981)	165SR13		•	26	24	26	24			4.50C-13
Princess (1979-81)	185/70SR14		•	26	24	26	24			4.5J-14
Ambassador (1982-83)	185/70SR14		•	26	24	26	24			4.5J-14
Metro 1.0; City (1983)	135SR12		•	32	28	32	28			4.50B-12
Metro 1.3 (1983)	155/70SR12		•	28	26	28	26			4.50B-12
Maestro 1.3 (1983)	145SR13		•	30	32	30	32			4.5J-13
Maestro 1.3L; HLE (1983)	155SR13		•	26	28	26	28			4.5J-13
Maestro 1.6L; HLE (1983)	165SR13		•	26	28	26	28			4.5J-13
Maestro Vanden Plas (1983)	175/65SR14		•	28	26	28	26			5.5J-14
Bentley										
'T' Series & LWB (without division) (1979-81)	235/70HR15		•	24	28	24	28	30	34	6JK-15
LWB (with division) (1979-81)	235/70HR15		•	24	30	24	30	30	36	6JK-15
Corniche (1979-83)	235/70HR15		•	24	28	24	28	30	34	6JK-15
Mulsanne (1981-83)	235/70HR15		•	24	28	30	34	30	34	6JK-15
BMW										
316; 318 (1979-80)	165SR13		•	26	26	27	29			5J/5.5J-13
	or 185/70HR13		•	26	26	27	29			5J/5.5J-13
316; Cabriolet (1981-83)	165SR13		•	27	27	29	31			5J/6J-13
320; 320i (1979-80)	165SR13		•	27	27	29	30			5J/5.5J-13
	or 185/70HR13		•	27	27	29	30			5J/5.5J-13
320; Cabriolet; 320i (1981-83)	185/70HR13		•	29	29	31	34			5J/6J-13
323C (1979-80)	185/70HR13		•	29	29	32	34			5.5J/6J-13
323i; Cabriolet (1981-83)	185/70HR13		•	29	29	31	34			5J/5.5J/6J-13
518 (1979-83)	175SR14		•	27	27	30	33			5.5J/6J-14
	or 195/70HR14		•	27	27	30	33			5.5J/6J-14
520; 520i (1979-80)	175SR14		•	27	27	30	33			5.5J/6J-14
	or 195/70HR14		•	27	27	30	33			5.5J/6J-14
520/6 (1979)	175HR14		•	30	30	32	36			5.5J/6J-14
	or 195/70HR14		•	29	29	29	33			5.5J/6J-14
525 (1979-1982)	175HR14		•	30	30	32	36			5.5J/6J-14
	or 195/70HR14		•	29	29	29	30			5.5J/6J-14
520i; 525 (1983)	175HR14		•	30	30	31	36			5.5J-14
	or 195/70HR14		•	28	28	31	33			5.5J-14
528i (1979-83)	195/70VR14		•	33	33	34	36			6J-14
528 (1980)	195/70HR14		•	30	30	32	34			6J-14
628 CSI (1981)	195/70VR14		•	34	37	34	37			6J-14
535i (1981)	195/70VR14		•	34	37	37	41			6J-14
628 CSI (1983)	195/70VR14		•	34	34	35	38			6J-14
632; 633 (1979-80)	195/70VR14		•	33	33	34	37			6.5J-14
633 CSI (1980)	195/70VR15	•		33	30	34	34			6J/7J-14
635 CSI; (1979-81)	195/70VR14		•	36	36	37	41			6.5J-14
635 CSI; (1981-82)	195/70VR14		•	31	31	33	37			6J-14
635 CSI; (1983)	195/70VR14		•	36	36	38	42			6.5J-14
728i; (1979-83)	195/70HR14		•	32	32	33	37			6J/6.5J-14
	or 205/70HR14		•	32	32	32	34			6J/6.5J-14
732i; (1979-83)	205/70HR14		•	32	32	33	37			6.5J-14
733i; (1979-80)	205/70VR14	•		32	32	33	37			6.5J-14
735i; (1979-82)	205/70VR14	•		32	32	33	37			6.5J-14
735i; 735iSE; (1983)	205/70VR14		•	31	31	33	37			6J-14
Bristol										
412; 603 (1979)	205VR15		•	28	28	30	30	30	30	6JK-15
412; 603 (1980)	205VR15		•	28	28	30	32	32	32	6JK-15
412; 603 (1981-82)	205VR15		•	29	29	31	31	31	31	6JK-15
Beaufighter (1979-80)	225/70VR15		•	28	28	30	30	30	30	6JK-15
Beaufighter (1981-83)	225/70VR15		•	29	29	31	31	31	31	6JK-15
Brigand; Brittania (1983)	225/70VR15		•	29	29	31	31	31	31	6JK-15
Citroen										
CV6; 2CV; 2CV6; (1979-1983)	125SR15		•	20	26	20	26			4J-15
	or 135SR15		•	20	26	20	26			4J-15
Dyane; Ami 8. (1979-1983)	125SR15		•	20	26	20	26			4J-15
	or 135SR15		•	20	26	20	26			4J-15
	or 155/70HR15		•	20	26	20	26			4J/4.5J-15
Visa Club (1979-80)	135SR13		•	25	29	25	29			4.5J-13
Visa Club (1981-83)	145SR13		•	25	28	25	28			4.50B-13
Visa Super (1979-83)	145SR13		•	25	29	25	29			4.5J-13
Ami-Super & Estate (1980)	135SR15		•	26	28	26	28			4J-15
	or 155/70HR15		•	26	28	26	28			4J-15
GS1015; 1220; Estate (1979-80)	145SR15		•	26	28	26	28			4.5J-15

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Citroen—cont.										
GSA range (1981-83)	145SR15		•	26	28	26	28			4.5J-15
CX Reflex; Athena (1979-80)	Front 185HR14		•	28		28				5.5J-14
	Rear 175HR14		•		30		30			5.5J-14
CX2200 Diesel Saloon (1979-80)	Front 185HR14		•	28		28				5.5J-14
	Rear 175HR14		•		30		30			5.5J-14
CX2200 Diesel Estate (1979-80)	185HR14		•	28	30	28	30			5.5J-14
CX2400 GTI; (1979-80)	185VR15		•	30	32	30	32			5.5J-14
CX2400 Saloon & Estate (1979-83)	185HR14		•	28	30	28	30			5.5J-14
Pallas; Prestige; GTI; Safari (1979-83)	Front 185HR14		•	28		28				5.5J-14
	Rear 175HR14		•		30		30			5.5J-14
CX Familiale (1981-83)	Front 185HR14		•	28		28				5.5J-14
	Rear 175HR14		•		30		30			5.5J-14
Colt										
Lancer 1200; 1400 (1979-80)	155SR13		•	23	24	23	24			4J/4.5J-13
Lancer 1600 (1979-82)	165SR13		•	24	24	28	28			4.5J-13
Lancer 1400 Estate (1980-82)	155SR13		•	23	30	23	30			4J-13
Celeste 1600 (1979-81)	165SR13		•	24	24	24	24			5J-13
	or 175/70SR13		•	24	24	24	24			5J-13
Celeste 2000 (1979-81)	175/70HR13		•	24	24	24	24			5J-13
Galant 1600; 2000 Estate (1980-82)	165SR13		•	24	32	24	32			4.5J-13
GTD (1980)	185/70HR13		•	24	30	24	30			5J-13
Galant 2000 (1981-82)	165SR14		•	27	27	27	29			5.5J-14
Galant 1600 (1981-82)	165SR13		•	27	27	27	27			5J-13
Galant 2000; Turbo (1983)	185/70HR14		•	27	27	27	29			5.5J-14
Sigma 1600 & 2000 (1979-82)	165SR13		•	27	27	27	27			5J-13
Sigma Estate 1600 (1980-81)	165SR13		•	31	31	31	31			5J-13
Sigma Estate 2000 (1979-82)	165SR14		•	27	33	27	33			5J-14
Sappora 2000 (1979-82)	195/70HR14		•	27	27	27	27			5J-14
Sappora Turbo (1983)	195/70HR14		•	27	27	28	28			5.5J-14
Tredia 1400; 1600 (1983)	165SR13		•	24	24	26	26			5J-13
Tredia 1600 Turbo (1983)	185/70HR13		•	27	27	28	28			5J-13
Cordia 1600 (1983)	165SR13		•	24	24	26	26			5J-13
Cordia 1600 Turbo (1983)	185/70HR13		•	27	27	28	28			5J-13
Mirage Turbo (1983)	165/70HR13		•	25	25	27	27			4.5J-13
Starion 2000 Turbo (1983)	205/70VR14		•	30	30	32	32			6J-14
	or 215/70VR14		•	30	30	32	32			6J-14
Daihatsu										
Charade (1979-83)	155SR12		•	24	24	24	24			4J-12
Domino (1982-83)	145SR10		•	26	26	26	26			3.50B-10
Charmant 1300 (1982-83)	155SR13		•	24	24	24	24			4J-13
	or 165SR13		•	24	24	24	24			4J-13
	or 175/70SR13		•	24	24	24	24			5J-13
Charmant 1600 (1982-83)	165SR13		•	24	24	24	24			4J-13
	or 175/70SR13		•	24	24	24	24			5J-13
Daimler										
Double Six; Vanden Plas (1979-80)	205/70VR15		•	28	26	29	30	36	36	6JK-15
Double Six; Vanden Plas (1981-83)	215/70VR15		•	36	32	36	32	36	36	6JK-15
Sovereign 3.4; 4.2 (1979-80)	ER70VR15		•	27	26	27	30	33	36	6JK-15
Sovereign 3.4; 4.2 (1981-83)	215/70VR15		•	33	32	33	32	33	36	6JK-15
Limousine (1979-83)	205HR15		•	28	28	30	35			6JK-15
Datsun										
Cherry 100A; F11 Range (1979-80)	600S12		•	24	24	28	28			4.5J-12
	or 155SR12	•		24	24	28	28			4.5J-12
	or 175/70HR12	•		24	24	28	28			5.5J-12
New Cherry range (1979-80)	155SR13		•	24	24	28	28			4.5J-13
	or 175/70SR13		•	24	24	28	28			4.5J-13
Cherry 3dr; 5dr (1981-82)	155SR13		•	24	24	32	32			4.5J-13
Cherry 1.0; 1.3 ranges (1983)	155SR13		•	26	26	26	26			4.5J-13
120Y range (1979-80)	615S13		•	24	24	27	27			4.5J-13
	or 155SR13	•		24	27	24	27			4.5J-13
	or 175/70SR13	•		24	24	24	24			4.5J/5J-13
Sunny range & Cherry 5dr Estate (1981-82)	155SR13		•	24	27	32	32			4.5J-13
Sunny 1.3; 1.5 range (1983)	155SR13		•	26	26	26	26			4.5J-13
140; 160 Saloon & Coupe (1979-80)	165SR13	•		26	26	26	26			4.5J-13
	or 185/70SR13	•		26	26	26	26			5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Datsun—cont.										
140; 160 Estates (1979-80)	165SR13	•		26	28	26	28			4.5J-13
	or 185/70SR13	•		26	28	26	28			5J/5.5J-13
Violet 1.4; 1.6 (1980-1982)	165SR13		•	26	26	33	33			4.5J-13
180B Mk2. & Estate (1979-80)	165SR14		•	28	28	28	28			5J-14
	or 185/70HR14		•	28	28	28	28			5.5J-14
Bluebird (1981-82)	165SR14		•	29	29	33	33			5J-14
	or 185/70SR14		•	26	26	34	34			5J-14
Bluebird Saloon (1983)	165SR14		•	28	28	28	31			5J-14
Bluebird Estate (1983)	165SR14		•	28	28	28	28			5J-14
200L Laurel (1979-80)	185/70SR14		•	24	24	28	28			5.5J-14
230S Laurel (1981-82)	185/70SR14		•	24	24	29	29			5.5J-14
C31 Laurel (1981-82)	185/70SR14		•	26	26	34	34			5.5J-14
Laurel 2.4 (1983)	185/70SR14		•	26	26	30	30			5.5J-14
240K Coupe (1979-80)	195/70HR14		•	27	24	31	28			5.5J-14
260C Saloon (1979-80)	195/70HR14		•	27	27	31	31			5J-14
260C Estate (1979-80)	195/70HR14		•	26	31	30	38			5J-14
Sky Line Coupe (1981-82)	195/70HR14		•	27	24	32	29			5.5J-14
260Z & 2+2 (1979-80)	195/70VR14		•	28	28	32	32			5.5J-14
280C Saloon (1979-80)	195/70HR14		•	27	27	31	31	31	34	5J-14
280C Estate (1979-80)	195/70HR14		•	24	30	28	34			5J-14
280C 430 Series (1981-82)	195/70HR14		•	29	29	34	34	34	34	5J-14
280C Saloon (1983)	195/70HR14		•	28	28	32	32	34	34	5.5J-14
280C Estate (1983)	195/70HR14		•	28	34	32	38			5J-14
280ZX (1979-80)	195/70VR14		•	28	28	32	32	32	32	5.5J-14
	or 205/70VR14		•	28	28	32	32	32	32	5.5J-14
	or 200/65HR370 Denovo		•	28	28	32	32	32	32	125 x 370 Denloc
280ZX S130 Series (1981-82)	195/70VR14		•	29	29	38	38	38	38	5.5J-14
	or 205/70VR14		•	29	29	38	38	38	38	5.5J-14
	or 200/65HR370 Denovo		•	29	29	34	34	34	34	125 x 370 Denloc
280ZX 2+2 (1983)	205/70VR14		•	28	28	32	32			6J-14
De Tomaso										
Pantera L (1979-80)	Front 185/70VR15	•		26		26		30		7L-15
	Rear 215/70VR15	•			30		30		34	8L/10L-15
Pantera GTS (1979-80)	Front CR70VR15	•		32		32		36		7L-15
	Rear HR70VR15	•			36		36		40	8L/10L-15
Deauville (1979-80)	215/70VR15	•		37	35	37	35	40	38	7L-15
Ferrari										
512 Boxer (1979-80)	Front 215/70VR15		•	37		37		42		7.5J-15
	Rear 225/70VR15		•		42		42		47	9.0L-15
308 GT4 2+2 (1979-80)	205/70VR14		•	25	28	30	34	31	37	7.5J-14
308 GTB (1979-80)	205/70VR14		•	27	34	27	34			7.5J-14
308 GTB (1981)	205/70VR14		•	32	34	32	34			7J-14
308 GT4 (1981)	205/70VR14		•	30	34	30	34	32	37	7J-14
308 (1982)	240/55VR390		•	33	35	33	35			165 x 390
	or Front 205/55VR16		•	33		33				
	Rear 225/55VR16		•		35		35			
365 GTC4 (1980)	215/70VR15		•	34	38	34	38	44	44	7.5L-15
365 GT4 2+2 (1980)	215/70VR15		•	40	47	40	47	46	50	7.5L-15
Dino 246 GT (1980)	205/70VR14		•	27	31	27	31			6.5J-14
Mondial (1982-83)	240/55VR390		•	33	35	33	35			165 x 390
400 (1982-83)	240/55VR390		•	36	36	36	36			165 x 390
Fiat										
126 (1979-83)	135SR12		•	20	28	20	28			4J-12
127 900 range (1979-83)	135SR13	•		24	27	24	27			400B-13
	or 165/70SR13	•		24	27	24	27			400B-13/5J-13
Panda (1982-83)	135SR13		•	26	29	26	29			400B-13
127 1050 range; Sport (1979-83)	135SR13	•		25	27	24	32			400B-13
	or 165/70SR13	•		25	27	24	32			400B-13
128-1100/1300 ranges (1979-80)	145SR13	•		26	24	26	24			4.5J/5J/5.5J-13
	or 165/70SR13	•		26	24	26	24			5.5J-13
128 (1981-83)	145SR13		•	24	24	27	27			4.5J-13
128 Berlinetta (1979-80)	145SR13	•		26	26	29	29			4.5J/5J/5.5J-13
	or 165/70SR13	•		26	26	29	29			5.5J-13
X1/9 (1979-83)	165/70SR13	•		24	28	24	28			5J-13
Strada 60; 65; 70 (1979-80)	145SR13	•		27	26	27	31			400B-13
	or 165/70SR13	•		27	26	27	31			400B-13
Strada (1981-82)	145SR13		•	26	24	26	24			4.5J-13
	or 165/70SR13		•	26	24	26	24			4.5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Fiat—cont.										
Strada (1983)	145SR13		•	27	26	30	29			4.5J-13
	or 165/70SR13		•	27	26	30	29			5J-13
131-1300; 1600 range (1979-80)	155SR13	•		26	29	26	29			4J/4.5J-13
	or 175/70SR13	•		26	29	26	29			5J/5.5J-13
Mirafiori 131 (1981-82)	165SR13		•	24	24	24	24			5J-13
Mirafiori 131 (1983)	155SR13		•	26	29	29	31			4.5J-13
	or 165SR13		•	26	29	29	31			5J-13
	or 175/70SR13		•	26	29	29	31			5J-13
	or 185/60HR14		•	24	24	24	24			5.5J-14
Mirafiori 131 Super (1983)	165SR13		•	26	26	29	29			5J-13
	or 175/70SR13		•	26	26	29	29			5J-13
	or 185/60HR14		•	26	26	29	29			5.5J-14
Mirafiori Sport (1979-80)	185/70SR13	•		26	28	26	28			5J-13
	or 185/60HR14	•		26	28	26	28			5J-14
Mirafiori Sport (1981-82)	185/60HR14		•	24	24	24	24			5.5J-14
Mirafiori Sport (1983)	185/70SR13		•	26	27	29	30			5.5J-13
	or 185/60HR14		•	26	27	29	30			5.5J-14
132-1600 Saloon (1979-80)	175/70SR14	•		27	29	27	29			5.5J-14
1800 (1979-80)	185/70SR13	•		26	27	26	27			5.5J-13
2000 (1979-80)	175/70SR14	•		27	29	27	29			5.5J-14
132 Range (1981-83)	185/70HR14		•	26	28	26	28			5.5J-14
Argenta (1983)	175/70SR14		•	27	27	28	28			5.5J-14
	or 185/65HR14		•	27	27	28	28			5.5J-14
Ford										
Fiesta 957cc Basic (1979-83)	135SR12		•	27	27	31	31			4.00C-12
Fiesta 957cc; 1100; 1300 (1979-83)	145SR12		•	23	26	26	28			4.00C-12
	or 155SR12		•	23	26	26	28			4.50C-12
Fiesta 1.3 Ghia; S. (1979-81)	155SR12		•	23	26	26	28			4.50C-12
Escort MkII 1100; 1300, 1600 (1979-80)	600-12		•	21	27	23	30			4.50C-12
	or 155SR12		•	21	27	24	36			4.5J-12
	or 155SR13		•	21	24	24	36			4.5J-13
	or 175/70SR13		•	21	24	23	28			4.5J/5J-13
Escort 1.1; 1.3; 1.6 (1981-	145SR13		•	26	26	28	33			4.5J-13
	or 155SR13		•	26	26	28	33			5J-13
	or 175/70SR13		•	26	26	28	33			5J-13
	or 185/60HR14		•	26	26	28	33			5.5J-14
XR3 (1981-82)	185/60HR14		•	28	28	28	28			5.5J-14
XR3 (1983)	185/60HR14		•	26	26	28	33			6J-14
Escort Mexico; RS1800; RS2000 (1979)	175/70SR13		•	24	27	26	28			5.5J-13
Escort Mexico (1980-81)	175/70SR13		•	21	24	23	28			5.5J-13
Escort RS1800; RS2000 (1980-81)	175/70SR13		•	24	22	24	24			5.5J/6J-13
Escort MkII Estate 1.3 (1979-80)	155SR13		•	21	24	24	36			4.5J-13
Capri MkII (1979-83)	165SR13		•	23	27	27	31			5J/5.5J-13
	or 185/70SR13		•	23	27	27	31			5.5J-13
Capri 2.8; 3.0 (1979-83)	185/70HR13		•	23	27	27	31			5.5J-13
Cortina 1.3; 1.6; 2.0; 2.3 (1979-83)	165SR13		•	26	26	28	36			4.5J-13
	or 185/70SR13		•	23	23	28	36			5.5J-13
Cortina 1.3; 1.6; 2.0 Estates (1979-83)	165SR13		•	26	26	28	40			4.5J-13
	or 185/70SR13		•	23	24	28	40			5.5J-13
Cortina 3.0 Estate (1981-83)	175SR13		•	21	24	28	40			5.5J-13
Granada MkII 2.3; 2.8 (1979-80)	175SR14		•	24	24	27	33			6J-14
	or 185SR14		•	24	24	27	33			6J-14
	or 195/70HR14		•	24	24	27	33			6J-14
Granada MkII Estate (1979-80)	185SR14		•	26	26	27	36			5J-14
	or 185HR14		•	26	26	27	36			5J-14
Granada 2.0 (1981-82)	175SR14		•	24	24	27	36			6J-14
Granada 2.3 (1981-82)	175HR14		•	26	26	27	36			6J-14
Granada 2.8 (1981-82)	185SR14		•	24	24	27	33			6J-14
	or 185HR14		•	24	24	27	33			6J-14
Granada 2.0; 2.3 Estates (1981-82)	185SR14		•	26	26	27	36			6J-14
Granada 2.8 Estate (1981-82)	185HR14		•	26	26	27	40			6J-14
Granada 2.0 (1983)	175SR14		•	24	24	27	36			6J-14
Granada 2.3 (1983)	175SR14		•	26	26	27	36			6J-14
Granada 2.8 (1983)	185SR14		•	24	24	27	33			6J-14
Granada 2.0 Estate (1983)	185SR14		•	26	26	27	36			6J-14
Granada 2.8 Estate (1983)	185HR14		•	26	26	27	40			6J-14

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Ford—cont.										
Sierra 1.3; 1.6; 2.0 (1983)	165SR13		•	26	26	29	36			4.5J-13
	or 185/70SR13		•	26	26	29	36			5.5J-13
Sierra 2.3D (1983)	165SR13		•	29	29	29	36			4.5J-13
	or 185/70SR13		•	29	29	29	36			5.5J-13
Sierra 1.6; 2.3 Estate (1983)	175SR13		•	26	26	29	40			5.5J-13
	or 195/70HR13		•	23	23	29	40			5.5J-13
Sierra XR4i (1983)	195/60VR14		•	26	26	29	36			5.5J-14
F.S.O. (Polski-Fiat)										
125 P Saloon (1979-82)	165SR13	•		24	28	24	28			4.5J/5J-13
	or 185/70SR13	•		24	28	24	28			5J/5.5J-13
125 P Estate (1979-82)	175SR13	•		24	28	24	34			4.5J-13
	or 195/70SR13	•		24	28	24	34			5J/5.5J-13
Polonez (1979-80)	175SR13	•		26	27	26	27			5J-13
Polonez (1981-83)	175SR13		•	26	29	26	29			5J-13
125 Pickup (1981-83)	175SR13		•	26	35	26	25			5J-13
1300; 1500 (1983)	165SR13		•	22	23	22	23			4.5J-13
1500 Estate (1983)	165SR13		•	22	24	22	24			4.5J-13
Ginetta										
G15 (1979-80)	145SR13	•		15	23	15	23	17	25	5.5J-13
	or 165/70SR13	•		15	23	15	23	17	25	5.5J-13
G21 (1979-80)	185/70HR13	•		20	22	20	22	22	24	5.5J-13
Honda										
Civic 1200; 1500 (1979-80)	155SR12		•	24	24	24	26			4J-12
Civic 1300 (1981-83)	155SR13		•	24	24	24	26			4J-13
Accord 1600 (1979-81)	155SR13		•	24	24	24	26			4.5J-13
Accord (1982-83)	165SR13		•	24	24	24	26			4.5J-13
Prelude (1979-82)	155SR13		•	24	24	24	24			4.5J-13
Prelude (1983)	155SR13		•	24	24	24	26			4.5J-13
Quintet (1981)	155SR13		•	24	24	24	24			4J-13
Quintet (1982-83)	155SR13		•	24	24	24	26			4J-13
Executive (1981)	155SR13		•	24	24	24	26			4.5J-13
Hyundai										
1200 & 1400 Saloon (1983)	155SR13		•	28	28	28	31			4.5J-13
1200 Pickup (1983)	155SR13		•	28	28	28	33			4.5J-13
Jaguar										
XJ6 (1979-80)	ER70VR15		•	27	26	27	30	33	36	6JK-15
XJ6 (1981-83)	205/70VR15		•	33	32	33	36	36	36	6JK-15
XJ12 (1979-81)	205/70VR15		•	28	26	29	30	36	36	6JK-15
XJ12HE (1982-83)	215/70VR15		•	36	32	36	32	36	36	6JK-15
XJS (1979-81)	205/70VR15		•	26	24	26	26	32	32	6JK-15
XJS HE (1982-83)	215/70VR15		•	32	32	32	32	32	32	6JK-15
Lada										
1200; 1300 Saloon (1979-80)	6.15S13	•		24	26	24	26			4.5J-13
	or 155SR13	•		24	26	24	26			4.5J-13
	or 175/70SR13	•		24	26	24	26			5J-13
1200 Estate (1979-80)	165SR13	•		24	26	24	30			5J-13
	or 185/70SR13	•		24	26	24	30			5J-13
1500 Saloon (1981-83)	165SR13	•		24	26	24	26			5J-13
	or 185/70SR13	•		24	26	24	26			5J-13
1500 Estate (1981-83)	165SR13	•		24	26	24	30			5J-13
	or 185/70SR13	•		24	26	24	30			5J-13
1600 Saloon (1979-83)	165SR13	•		24	27	23	27			5J-13
1600 Estate (1981-83)	165SR13	•		23	27	23	27			5J-13
Lamborghini										
Urraco (1979-80)	205/70VR14	•		32	34	32	34	34	36	7.5L-14
Espada; Jamarn (1979-80)	215/70VR15	•		32	34	32	34	34	36	7.5L-15
Countach (1979-80)	Front 205/70VR14	•		32		32		34		7.5L-14
	Rear 230/70VR14	•			34		34		36	9.5L-14
Lancia										
Beta 1300 (1979-80)	155SR14	•		24	24	27	27	31	31	5J-14
	or 175/70SR14	•		24	24	27	27	31	31	5J/5.5J-14
(1981-83)	155SR14		•	24	24	28	28	31	31	5J-14
Beta 1600 (1979-80)	175/70SR14	•		24	24	27	27	31	31	5.5J-14
(1981-83)	175/70SR14		•	24	24	28	28	31	31	5.5J-14
Beta 2000; HPE (1979-83)	175/70SR14	•		24	24	27	27	32	32	5.5J-14
Beta Monte Carlo (1979)	185/70HR13	•		24	27	24	27			5.5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Lancia—cont.										
Beta Spyder (1979-81)	175/70SR14	•		24	24	27	27	31	31	5.5J-14
(1982-83)	175/70SR14		•	25	25	28	28	31	31	5.5J-14
Gamma (1979-83)	185/70HR14		•	26	26	30	30	34	34	6J-14
Lonsdale										
All Models	BR78S14		•	28	28	28	30			5J/5.5J-13
	or 165SR14									
	Reinforced		•	31	31	31	33			
Lotus										
Elite 501/502 (1979-83)	205/60VR14		•	22	22	30	32	30	32	7JK-14
Eclate (1981-83)	205/60VR14		•	20	22	30	32	30	32	7JK-14
Elite 503/504 (1979-80)	205/60VR14		•	18	20	30	32	30	32	7JK-14
Eclate 520 (1979-80)	185/70HR13		•	20	22	30	32	30	32	7JK-14
Eclate 521/522 (1979-80)	205/60VR14		•	20	22	30	32	30	32	7JK-14
Eclate 523/524 (1979-80)	205/60VR14		•	18	20	30	32	30	32	7JK-14
Esprit (1979-83)	Front 205/60VR14		•	18		18		24		7JK-14
	Rear 205/70VR14		•		27		27		33	7.5JK-14
Maserati										
Ghibli (1979-80)	215/70VR15		•	27	27	27	27	36	36	7.5L-15
Indy (1979-80)	205/70VR14	•		27	27	27	27	36	36	7.5L-14
Bora (1979-80)	Front 205/70VR15	•		33		33		35		7.5L-15
	Rear 215/70VR15	•			40		40		42	7.5L-15
Merack (1979-80)	Front 185/70VR15	•		33		33		35		7.5L-15
	Rear 205/70VR15	•			36		36		38	7.5L-15
Kyalami (1983)	205/70VR15		•	34	32	37	34			7.5L-15
Khamsin (1983)	215/70VR15		•	34	37					7.5L-15
Merack (1983)	Front 195/70VR15		•	21		32				7.5L-15
	Rear 215/70VR15		•		21		36			7.5L-15
Mazda										
1300 Hatchback (1979-80)	155SR13		•	24	28	24	30			4.5J-13
	or 175/70SR13		•	24	28	24	30			4.5J-13
1400 (1979-80)	175/70SR13		•	24	28	24	28			5J-13
1400 Estate (1979-81)	155SR13		•	24	28	24	28			4.5J-13
1000 Saloon (1980)	155SR13	•		26	26	26	30			4.5J/5J-13
	or 175/70SR13	•		26	26	26	30			5J-13
Montrose 1600 (1979-81)	165SR13		•	26	28	26	28			5J-13
Montrose 2000	185/70SR13		•	26	28	26	28			5.5J-13
Montrose 2000 Estate (1979-81)	175SR14		•	26	32	26	32			5.5J-14
RX7 (1979-83)	185/70HR13		•	26	26	26	26			5.5J-13
818 Saloon (1980)	165SR13		•	26	28	26	28			4.5J-13
818 Estate (1980)	165SR13		•	26	28	26	30			4.5J-13
616 Saloon (1980)	165SR13		•	26	26	26	26			4.5J-13
929 Saloon; Coupe (1980)	175SR13		•	24	24	28	28			5.5J-13
	or 195/70SR13		•	24	24	28	28			5.5J-13
929 Estate (1980-81)	175SR13		•	24	28	24	28			5J-13
	or 195/70SR13		•	24	28	24	28			5J/5.5J-13
929 Estate (1982-83)	175SR14		•	26	32	26	32			5.5J-14
323 1100; 1300; 1500 (1981-83)	155SR13		•	26	26	26	26			4.5J-13
323 1500GT (1981-83)	175/70SR13		•	26	26	26	26			5J-13
323 Estate (1981-83)	155SR13		•	26	26	26	30			4.5J-13
626 1.6 Saloon (1982-83)	165SR13		•	26	28	26	28			5J-13
626 2.0 Saloon; Coupe (1982)	185/70SR13		•	26	28	26	28			5.5J-13
626 2.0 Saloon (1983)	185/70SR14		•	26	28	26	28			5.5J-14
626 1.6 FWD (1983)	165SR13		•	28	26	30	28			5J-13
626 2.0 FWD (1983)	185/70HR14		•	28	26	30	28			5.5J-14
Mercedes Benz										
200D; 240D; 300D (Type W123) (1979-83)	175SR14		•	29	32	29	32	33	36	5.5J-14
	or 195/70HR14		•	29	32	29	32	33	36	6J-14
200; 230 (Type W123) (1979-83)	175SR14		•	29	32	29	32	33	36	5.5J-14
	or 195/70HR14		•	29	32	29	32	33	36	6J-14
250 (Type W123) (1979-83)	175HR14		•	29	32	29	32	33	36	5.5J-14
	or 195/70HR14		•	29	32	29	32	33	36	6J-14
240D LWB; 250LWB (Type W123) (1979-83)	185HR15		•	30	38	30	38	30	40	5.5J-15
230C; 280; 280C; 280E; 280CE (1979-83)	195/70HR14		•	29	32	29	32	33	36	6J-14
230T; 230TD; 300TD Estates (1979-83)	195/70SR14		•	29	32	29	36	33	36	6J-14
250T; 280TE Estates (1979-83)	195/70HR14		•	29	32	29	32	33	36	6J-14

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Mercedes Benz—cont.										
280S; 280SE (1979-83)	185HR14		•	30	33	33	36	34	38	6J-14
	or 205/70HR14		•	30	33	33	36	38	40	6J-14
350SE (1979-81)	205/70HR14		•	30	33	33	36	38	40	6.5J-14
350SL (1979-80)	205/70HR14		•	32	36	32	36	34	37	6.5J-14
450SL; SLC (1979-80)	205/70VR14		•	32	36	32	36	38	40	6.5J-14
450SE; SEL (1979-80)	205/70VR14		•	33	36	33	36	38	40	6.5J-14
450SEL 6-9 (1979-80)	215/70VR14		•	32	32	35	35	38	38	6.5J-14
220D LWB; 230LWB (1979)	185HR15	•		30	36	30	36			5.5J-15
600 (1980)	900H15 6/8ply		•	28	30	28	32	32	36	6.5J-15
600 long (1980)	900H15 8ply		•	30	32	32	36	36	40	6.5J-15
230TE (1981-83)	195/70HR14		•	28	32	28	36	33	36	6J-14
240TD (1981-83)	195/70SR4		•	28	32	28	36	33	36	6J-14
380SE; SEL; 500SE; SEL (1981-83)	205/70VR14		•	28	32	28	32	35	37	6.5J-14
280SL; 350SL (1981-83)	195/70HR14		•	28	32	32	36	35	39	6.5J-14
380SL; 500SL (1981-83)	205/70VR14		•	28	32	32	36			6.5J-14
280GE (1983)	205R16		•	26	28	28	32			5.5J-16
	or 235/70HR15		•	26	28	28	32			5.5J-15
500SEC (1983)	205/70VR14		•	32	39	35	42			6.5J-14
190 (1983)	175/70HR14		•	26	28	28	33			5J-14
190E (1983)	175/70HR14		•	28	32	32	36			5J-14
280G 4WD (1983)	205R16 M & S		•	26	29	29	32			5.5JK-16
300G 4WD (1983)	205R16 M & S		•	26	30	29	32			5.5JK-16
MG										
Midget 1500 (1979-80)	145SR13		•	22	24	22	26	26	30	4.5J-13
MGB Roadster (1979-80)	165SR14		•	21	24	21	24	27	32	5J-14
	or 185/70SR14		•	21	24	21	24	27	32	5.5J/6J-14
MGB GT (1979-80)	165SR14		•	21	24	21	26	27	32	5J-14
	or 185/70SR14		•	21	24	21	26	27	32	5.5J/6J-14
Metro 1.0 (1981-82)	135SR12		•	32	28	32	28			4.50B-12
Metro 1.3 (1982-83)	155/70SR12		•	28	26	28	26			4.50B12
Metro Turbo (1983)	165/60HR13		•	28	28	28	28			5.5J-13
Maestro (1983)	175/65SR14		•	28	26	28	26			5.5J-14
Mini										
City; 850; 1000 (1979-83)	145SR10		•	28	26	28	26			3.50B-10
	or 165/70HR10		•	24	26	24	26			4.5J-10
Clubman 1000; 1100 (1979-83)	145SR10		•	28	26	28	26			3.50B-10
	or 165/70HR10		•	24	26	24	26			4.5J-10
1100 Special (1979)	165/70SR10		•	24	26	24	26			5J-10
1275GT (1979-81)	155/65SR310 Denovo		•	26	24	26	24			80 x 310
	or 145/70SR12		•	28	28	28	28			4.5J-12
Estate (1982-83)	145SR10		•	28	26	28	26			3.50B-10
City E (1983)	145SR10		•	28	26	28	26			3.50B-10
Mayfair (1983)	145SR10		•	28	26	28	26			3.50B-10
	or 165/70SR10		•	24	26	24	26			4.5J-10
Morgan										
4/4 1600 (1979-80)	165SR15	•		18	18	18	18			4.5J-15
Plus 8 (1979-81)	195/70VR14	•		20	20	20	20			5.5J-14
4 + 4 (1981-83)	165SR15	•		18	18	18	18			4.5J-15
	or 195/70VR15	•		20	20	20	20			5J-15
Plus 8 (1982-83)	195/70VR15	•		20	20	20	20			5.5J-15
Morris										
Marina 1300 Saloon (1979-80)	145SR13		•	26	28	26	28			4.50C-13
Estate (1979-80)	155SR13		•	26	28	26	32			4.50C-13
Marina 1700 Saloon (1979-80)	155SR13		•	26	28	26	28			4.50C-13
Estate (1979-80)	155SR13		•	26	28	26	32			4.50C-13
Ital 1300 Saloon (1981-83)	155SR13		•	26	28	26	28			4.50C-13
Estate (1981-83)	155SR13		•	26	28	26	28			4.50C-13
Ital 1700 Saloon (1981-83)	155SR13		•	26	28	26	28			4.50C-13
Estate (1981-83)	155SR13		•	26	28	26	28			4.50C-13
Ital 2000 Estate (1981-83)	155SR13		•	26	32	26	32			4.50C-13
Opel										
Kadett LS; GL Saloon (1979-80)	155SR13		•	24	24	27	32			5J-13
	or 175/70SR13		•	24	24	27	32			5J-13
Kadett LS; GL Estate (1979-80)	155SR13		•	24	29	26	33			5.5J-13
	or 175/70SR13		•	24	29	26	33			5.5J-13
Kadett SR (1979-80)	185/60HR14		•	26	29	29	32			5.5J-14
Ascona 1.6; 1.9 (1979-80)	165SR13		•	24	24	29	32			5J-13
	or 185/70SR13		•	23	23	26	26			5.5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Opel—cont.										
Ascona 2.0 (1979-83)	185/70HR13		•	23	23	26	26			5.5J-13
Manta Coupe (1979-82)	165SR13		•	24	24	29	32			5.5J-13
	or 185/70SR13		•	24	24	29	32			5.5J-13
Manta SRB; (1979-)	185/70SR13		•	24	24	26	26			5.5J-13
Manta 2.0; GTS (1979-83)	185/70HR13		•	26	26	29	29			5.5J-13
	or 195/70HR13		•	26	26	29	29			6J-13
Rekord 4dr. (1979-82)	175SR14		•	26	26	26	26	29	32	5.5J-14
	or 185/70SR14		•	23	23	26	29			5.5J-14
Rekord Diesel (1979-82)	175SR14		•	29	29	29	29	29	34	5.5J-14
	or 185/70SR14		•	26	26	29	36			5.5J-14
Senator (1979-83)	175HR14		•	32	32	36	40			6J-14
	or 195/70HR14		•	32	32	36	40			6J-14
Monza (1979-80)	205/60VR15		•	32	32	36	40			6J-15
Commodore GS (1980-81)	175HR14		•	26	26	32	34	32	32	6J-14
	or 195/70HR14		•	26	26	32	34	32	32	6J-14
GSE (1980-81)	195/70VR14		•	26	26	32	37	32	32	6J-14
Monza (1981-83)	175HR14		•	32	32	36	40			6J-14
	or 185/70HR14		•	32	32	36	40			6J-14
	or 205/60VR15		•	32	32	36	40			6J-15
Commodore (1982-83)	175HR14		•	29	29	32	37			6J-14
	or 195/70HR14		•	29	29	32	37			6J-14
Rekord (1983)	175HR14		•	26	26	29	32			5.5J-14
	or 185/70SR14		•	26	26	29	32			5.5J-14
Ascona 1.3 (1982-83)	165SR13		•	24	24	29	33			5J/5.5J-13
Kadett 1200 (1981-83)	145SR13		•	26	30	29	33			4.5J-13
Kadett GL (1981-83)	155SR13		•	24	26	29	33			4.5J-13
	or 175/70SR13		•	23	27	26	30			5.5J-13
Kadett Berlina (1982-83)	185/60HR14		•	26	29	29	32			5.5J-14
Panther										
Rio Especial (1979-80)	175/70HR13		•	22	24	22	24			5.5J-13
Lima (1979-83)	175/70HR13		•	22	24	22	24	24	26	5.5J-13
J72 (1979-83)	ER70VR15	•		26	26	26	26			6J-15
Deville 4.2 (1979-80)	HR70HR15	•		26	26	26	26			6J-15
Deville V12 (1979-80)	HR70HR15	•		26	26	26	26			6J-15
Deville (1981-82)	215/70VR15		•	26	26	26	26			6J-15
Peugeot										
104 ZL (1979)	135SR13	•		27	33	27	33			4.00B-13
104 GL (1979-83)	135SR13	•		27	32	27	32			4.00B-13
104 (others) (1979-81)	145SR13	•		27	32	27	32			4.50B-13
104 SR; SZ (1982-83)	145SR13		•	26	30	26	30			4.50B-13
	or 165/70SR13		•	26	30	26	30			5.00B-13
304 (1979-81)	145SR14	•		26	31	26	38			4.5J-14
	or 155SR14		•	27	31	27	31			4.50B-14
304 (1979-81)	145SR14	•		26	31	26	38			4.50B-14
	or 155SR14		•	27	31	27	31			4.50B-14
305 (1979-81)	145SR14	•		26	30	26	30			4.5J-14
305 (1982-83)	145SR14		•	26	30	26	30			4.5J-14
	or 155SR14		•	27	30	27	30			4.5J-14
404 (1981-83)	185SR15		•	21	48	21	48			5J-15
504 GR (1979)	175SR14	•		26	30	26	30			5J-14
	or 195/70HR14	•		26	30	26	30			5J-14
504 GR Estate (1979-80)	185SR14 Reinforced	•		23	26	23	46			5J-14
504 Family (1979-80)	185HR14	•		23	33	23	40			5J-14
504 TI (1980)	175HR14	•	•	23	28	23	28			5J-14
	or 195/70HR14	•	•	23	28	23	28			5J-14
504 C2 (1981-83)	175SR14		•	23	27	23	27			5J-14
	or 185SR14		•	23	46	23	46			5J-14
504 ER (1981-83)	165SR14		•	26	30	26	30			5J-14
	or 175SR14		•	26	29	26	29			5J-14
	or 185SR14		•	23	44	23	44			5J-14
505 Petrol (1979-83)	175HR14		•	23	28	23	28			5J-14
505 Diesel (1979-81)	175HR14		•	26	29	26	29			5J-14
604 Petrol (1979-80)	175HR14	•		26	30	26	30			5.5J-14
604 Diesel (1979-80)	175HR14	•		27	30	27	30			5.5J-14
604 (1981-83)	175HR14		•	26	30	26	30			5.5J-14
	or 185HR14		•	26	30	26	30			5.5J-14
Porsche										
911 SC (1979-83)	Front 185/70VR15		•	29		29				6J-15
	Rear 215/60VR15		•		34		34			7J-15

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Porsche—cont.										
911 SC Sport (1979-83)	Front 205/55VR16		•	29		29				7J-16
	Rear 225/50VR16		•		35		35			7J-16
Turbo (1979-80)	Front 205/55VR16		•	29		29				7J-16
	Rear 225/50VR16		•		43		43			8J-16
924 Coupe (1979-81)	165HR14		•	29	29	29	29			5.5J-14
	or 185/70HR14		•	29	29	29	29			5.5J/6J-14
924 (1982-83)	185/70HR14		•	29	29	29	29			6J-14
	or 205/60HR15		•	29	29	29	29			6J-15
Turbo (1979-83)	185/70VR15		•	29	36	29	36			6J-15
	or 205/55HR16		•	29	36	29	36			6J-16
924 Carrera GT (1983)	215/60VR15		•	29	36	29	36			7J-15
	or 205/55VR16 (Front)		•	29		29				7J-16
	215/50VR16 (Rear)		•		36		36			7J-16
928 (1979-80)	225/50VR16		•	35	35	35	35			7J-16
928S (1981-83)	225/50VR16		•	35	44	35	44			7J-16
928 (1981-83)	215/60VR15		•	36	43	36	43			7J-15
944 (1983)	Front 185/70VR15		•	29		29				7J-15
	Rear 215/60VR15		•		36		36			7J-15
Reliant										
Kitten (1979-83)	145SR10		•	20	22	20	24			3.50B-10
Robin (1979-80)	5.20-10		•	30	24	30	30			3.50B-10
Scimitar (1979-80)	185HR14	•		20	20	20	24			5.5J-14
	or 205/70HR14	•		20	20	20	24			5.5J-14
Scimitar (1981-83)	185HR14		•	24	24	24	24			5.5J-14
	or 205/70HR14		•	24	24	24	24			5.5J-16
Rialto (1983)	520-10		•	30	24	30	30			3.50B-10
	or 145SR10		•	30	24	30	30			3.50B-10
Renault										
4 range (1979-81)	135SR13	•		20	25	22	26			4.00B-13
	or 145SR13	•		20	25	22	26			4.00B-13
4 range (1982-83)	135SR13		•	20	26	22	26			4.00B-13
	or 145SR13		•	20	27	22	30			4.00B-13
5 Gordini (1979-83)	155/70SR13		•	26	29	26	29			5.5J-13
5 range (1979-81)	135SR13	•		25	28	28	30			4.00B-13
	or 145SR13	•		25	28	28	30			4.00B-13
5 range (1982-83)	135SR13		•	24	27	27	30			4.00B-13
	or 145SR13		•	24	27	26	32			4.00B-13
6 850cc (1980-81)	135SR13	•		21	24	24	27			4.00B-13
	or 145SR13	•		21	24	24	27			4.00B-13
	or 155/70SR13	•		21	24	24	27			4.50B-13
6 1100cc (1980-81)	145SR13	•		20	24	21	26			4.00B-13
	or 155/70SR13	•		20	24	21	26			4.50B-13
9 range (1982-83)	145SR13		•	24	27	26	29			4.5J-13
	or 155SR13		•	24	27	26	29			5.5J-13
	or 175/70SR13		•	24	27	26	29			5.5J-13
12 (1979-80)	145SR13	•		23	26	26	29			4.50B-13
	or 165/70SR13	•		23	26	26	29			5J-13
R12 (1981-82)	145SR13		•	23	26	26	29			4.50B-13
	or 155SR13		•	23	26	24	29			4.50B-13
	or 165SR13		•	23	27	24	29			4.50B-13
14 (1979-83)	145SR13		•	25	28	26	29			4.50B-13
15 (1980-81)	155SR13	•		26	28	28	31			4.50B-13
	or 165SR13	•		27	29	29	30			4.50B-13
16 TLM; TS (1980-81)	145SR14	•		23	28	26	31			4.5J-14
	or 185/70SR14	•		23	28	26	31			5.5J-14
16 TLA; TSA (1980-81)	155SR14	•		24	29	27	31			4.5J-14
	or 185/70SR14	•		24	29	27	31			5.5J-14
16 TX (1980)	155SR14	•		24	31	26	31			4.5J-14
	or 185/70SR14	•		24	31	26	31			5.5J-14
R18 (1981-83)	145SR13		•	24	26	27	29			4.50B-13
	or 155SR13		•	24	26	27	29			4.50B-13
	or 165SR13		•	24	28	26	29			4.50B-13
	or 185/70HR13		•	29	32	30	33			5.5J-13
17 TLM (1980-81)	155SR13	•		26	28	28	31			4.50B-13
	or 175/70SR13	•		26	28	28	31			5.5J-13
17 TL Auto (1980-81)	155SR13	•		28	28	30	31			4.50B-13
	or 175/70SR13	•		28	28	30	31			5.5J-13
17 TS (1980-81)	165HR13	•		27	30	28	31			5.50B-13
	or 185/70HR13	•		27	30	28	31			5.50B-13
20 TL Saloon (1979-83)	165SR13		•	28	28	30	31			5.50B-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
Renault—cont.										
TS (1979-83)	165SR14		•	29	29	32	32			5.50B-14
30 (1979-83)	175HR14	•		26	28	29	31			5.5J-14
	or 185HR14		•	26	29	29	32			5.5J-14
Fuego (1981-83)	175/70SR13		•	27	30	29	32			5.00B-13
	or 155SR13		•	28	29	27	30			5.00B-13
	or 185/65HR14		•	29	32	30	33			5.50B-13/5.5J-13
	or 185/70HR13		•	29	32	30	33			5.50B-13
Rolls Royce										
Silver Shadow (1979-80)	235/70HR15		•	24	28	24	28	30	34	6JK-15
Silver Wraith (1979-80)	235/70HR15		•	24	28	24	28	30	36	6JK-15
Silver Wraith (with Div) (1979-80)	235/70HR15		•	24	30	24	30	30	34	6JK-15
Corniche; Carmargue (1979-83)	235/70HR15		•	24	28	24	28	30	34	6JK-15
Silver Spirit; Spur (1981-83)	235/70HR15		•	24	28	24	28	30	34	6JK-15
Rover										
2000 (1982-83)	175HR14		•	26	28	30	32			5.5J-14
2300 SDI (1979-83)	175HR14		•	28	30	30	32			5.5J-14
	or 195/70HR14		•	28	30	30	32			5.5J-14
2400 SD Turbo (1983)	175HR14		•	28	30	30	32			5.5J-14
2600 SDI (1979-83)	175HR14		•	28	30	30	32			5.5J-14
	or 195/70HR14		•	28	30	30	32			5.5J-14
3500 SDI (1979-83)	185HR14		•	26	26	26	30			6J-14
	or 195/70HR14		•	26	26	26	30			6J-14
3500 Vitesse (1983)	205/60VR15		•	24	26	24	30			6J-15
Range Rover (1979-83)	205HR16	•		25	25	25	35			6JK-16
Saab										
99 (1979-83)	165SR15		•	27	27	30	30			5J-15
	or 175/70SR15		•	27	27	30	30			5J-15
99 EMS (1979-82)	175/70HR15		•	27	27	30	30			5J-15
99 Turbo (1979-81)	195/60HR15		•	28	28	31	34			5.5J-15
900 (1979-80)	165SR15		•	27	27	30	30			5J-15
	or 175/70SR15		•	27	27	30	30			5J-15
900 (1981-83)	165SR15		•	27	27	31	34			5J-15
	or 175/70SR15		•	27	27	31	34			5J-15
900 EMS (1979-80)	175/70HR15		•	27	27	30	30			5J-15
900 EMS (1981-83)	175/70HR15		•	27	27	31	34			5J-15
900 Turbo (1979-80)	195/60HR15		•	28	28	31	34			5.5J-15
900 Turbo (1981-83)	195/60HR15		•	27	28	30	31			5.5J-15
Skoda										
S110R Coupe (1979-80)	155SR14	•		20	26	22	28			4.5J-14
Super Estelle (1979-80)	165SR13		•	22	24	22	24			4.5J/5.5J-13
105; 120 (1981-83)	165SR13		•	20	26	26	30			4.5J/5.5J-13
Subaru										
1600 Saloon (1979-83)	155SR13		•	27	27	27	27			4.5J-13
1600 Estate (1979-83)	155SR13C 6pr		•	27	27	27	32			4.5J-13
1800 (1981-82)	155SR13		•	27	27	27	27			4.5J-13
1800 (1983)	175/70SR13		•	30	30	30	32			5J-13
1800 4WD (1983)	155SR13C 6pr		•	30	30	30	30			5J-13
	or 175/70SR13		•	30	30	30	30			5J-13
1800 MV (1981-83)	155SR13C 6pr		•	27	27	30	38			4.5J-13
Suzuki										
SC1000 (1979-83)	145/70SR12		•	20	31	20	31			4J-12
LJ800 (1980-83)	600-16 4pr		•	17	17	17	26			4.50E-16
Alto Fx (1982-83)	145/70SR12		•	27	27	27	27			4J-12
ST90K (1982-83)	14SR12C 6pr		•	23	23	26	40			4J-12
SJ410 (1983)	195SR15		•	20	20	20	26			5.5J-15
Talbot										
Horizon LS; GL (1979-83)	145SR13		•	26	26	30	30	30	32	4.5J-13
	or 165/70SR13		•	26	26	30	30	30	32	4.5J-13
GLS (1979-83)	175/70SR13		•	26	26	26	30	30	32	5J-13
SX (1979-83)	155SR13		•	26	26	30	30	30	32	5J-13
	or 175/70SR13		•	26	26	26	30	30	32	5J-13
Sunbeam 930 (1979-83)	145SR13		•	21	25	22	32			4.5J-13
	or 155SR13		•	22	22	22	28	24	30	4.5J-13
	or 175/70SR13		•	22	22	22	28	24	30	5J-13
1300 (1979-83)	155SR13		•	22	22	22	28	24	30	4.5J-13
	or 175/70SR13		•	22	22	22	28	24	30	5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
1600 (1979-83)	155SR13		•	22	22	22	28	24	30	4.5J-13
	or 175/70SR13		•	22	22	22	28	24	30	5J-13
1600 TI (1979-83)	175/70SR13		•	24	24	24	32	28	36	5.5J-13
Lotus (1980-83)	185/70HR13		•	27	33	27	33			6J-13
Alpine (1979-83)	155SR13		•	26	26	28	29	28	29	5J-13
	or 165SR13		•	26	26	28	29	28	29	5J-13
	or 175/70SR13		•	26	26	28	29	28	29	5J-13
	or 185/70SR13		•	26	26	28	29	28	29	5J-13
Avenger Saloon (1979-82)	155SR13		•	22	22	22	28			4.5J/5.5J-13
	or 175/70SR13		•	22	22	22	28			5J/5.5J-13
Estate (1979-82)	155SR13		•	24	24	24	36			4.5J-13
	or 175/70SR13		•	24	24	24	36			5J/5.5J-13
2 Litre (1979-81)	175HR14	•		22	23	23	26			5.5J-14
Rancho (1979-83)	185/70HR14	•		26	32	28	40	28	40	5.5J-14
Hunter (1979-80)	155SR13		•	24	24	26	30			4.5J-13
	or 175/70SR13		•	24	24	26	30			5.5J-13
Solara LS; GLS (1981)	155SR13		•	26	26	27	29	28	29	5.5J-13
SX (1981)	165SR13		•	26	26	28	29	28	29	5.5J-13
Solara LS; GLS (1982-83)	155SR13		•	26	26	28	29	28	29	5.5J-13
	or 175/70SR13		•	26	26	28	29	28	29	5.5J-13
SX (1982-83)	165SR13		•	26	26	28	29	28	29	5.5J-13
	or 185/70SR13		•	26	26	28	29	28	29	5.5J-13
Tagora 2.2 (1982-83)	175SR14		•	25	29	26	32	26	32	5.5J-14
	or 195/70SR14		•	25	29	26	32	26	32	5.5J-14
V6 (1982-83)	175SR14		•	26	30	28	34	28	34	5.5J-14
	or 195/70SR14		•	26	30	28	34	28	34	5.5J-14
Samba (1982-83)	135SR13		•	28	29	30	32	30	32	4.00B-13
	or 145SR13		•	26	28	29	30	29	30	4.00B-13
	or 165/70SR13		•	25	29	27	32	27	32	4.00B-13
Toyota										
Starlett 1000 (1979-83)	145SR13		•	24	24	28	28			4.5J-13
1200 (1979-83)	155SR13		•	24	24	28	28			4.5J-13
Corolla (1979-83)	155SR13		•	24	24	24	26			4.5J-13
	or 175/70SR13		•	24	24	24	26			5.5J-13
Corolla Liftback (1979-83)	155SR13		•	24	28	28	32			4.5J-13
	or 165SR13		•	24	28	28	32			5J-13
	or 175/70SR13		•	24	28	28	32			5.5J-13
Carina Saloon (1979-83)	165SR13		•	24	24	28	28			4.5J-13
	or 185/70SR13		•	24	24	28	28			5.5J-13
Estate (1979-83)	165SR13		•	24	26	28	32	28	37	4.5J-13
	or 185/70SR13		•	24	26	28	32	28	37	5.5J-13
Celica 1600 (1979)	165SR13		•	24	24	28	28			4.5J-13
	or 185/70SR13		•	24	24	28	28			5.5J-13
2000 (1979-83)	185/70HR14		•	24	24	28	28			5.5J-14
2000 Liftback (1979-83)	165SR14		•	24	27	27	30			5.5J-14
	or 185/70SR14		•	24	27	27	27			5.5J-14
Cressida Saloon (1979-83)	175SR14		•	24	24	28	28			5J-14
Estate (1979-83)	175SR14		•	23	28	27	32			5J-14
Crown Saloon (1979-82)	185SR14		•	26	28	28	30			5.5J-14
Estate (1979-80)	185SR14 Reinforced		•	28	30	32	36			5.5J-14
Crown Saloon (1983)	195/70HR14		•	27	27	27	27	28	28	5.5J-14
Corona 2000 Saloon (1979-81)	175SR14		•	26	26	28	32			5J-14
Liftback (1979-81)	175SR14		•	24	24	28	28			5J-14
Estate (1979-80)	175SR14		•	26	28	30	36			5J-14
Landcruiser FJ40/42 (1981-83)	205SR16	•		25	32	29	37			5.50F-16
FJ46/60 (1981-83)	205SR16	•		25	37	29	40			5.50F-16
Hi-Lux 4.4 (1981-83)	205SR16 Rein.	•		25	35	25	44			5.50F-16
Tercel (1983)	145SR13		•	24	24	27	27			4.5J-13
	or 155SR13		•	24	24	27	27			4.5J-13
Tercel 4 x 4 (1983)	165SR13		•	26	26	26	26			5J-13
Camry 1.7 GL (1983)	165SR13		•	30	30	30	30			5J-13
Triumph										
Dolomite (1979-81)	155SR13		•	26	30	26	30			4J-13
	or 175/70SR13		•	26	30	26	30			4.5/5J-13
Sprint (1979-81)	175/70HR13		•	22	24	22	24			5.5J-13
Spitfire 1500 (1979-81)	155SR13		•	21	26	21	26			4.5J-13
TR7 4 speed (1979-81)	175/70SR13		•	24	28	24	28			5.5J-13
5 speed (1979-81)	185/70HR13		•	24	28	24	28			5.5J-13
TR8 (1979)	185/70HR13		•	24	28	28	28			5.5J-13
Acclaim HL; HLS (1982-83)	165/70SR13		•	24	24	24	28			4.5J-13
CD (1982-83)	165/70SR13		•	24	24	24	28			4.5J-13

Tyre/Wheel Equipment and Inflation Pressures for Cars 1979-1983

Make & Model	Tyre Details			Inflation Pressures (p.s.i.)						Wheel Details
	Size	Type		Normal		Fully Laden		High Speed		
		Tubed	Tubeless	Front	Rear	Front	Rear	Front	Rear	
TVR										
2500M; 3000M; ML (1979-80)	185HR14		•	24	26	24	26			6J-14
Tasmin (1981-83)	205/60VR14		•	22	24	22	24			6J-14
Vauxhall										
Chevette Saloon (1979-83)	155SR13		•	21	25	22	29			5J-13
	or 175/70SR13		•	21	25	22	29			5.5J-13
Estate (1979-83)	155SR13		•	21	25	24	34			5J-13
	or 175/70SR13		•	21	25	24	24			5.5J-13
HS2300 (1979-83)	205/60HR13		•	28	24	28	27			6J-13
Viva (1979-80)	155SR13		•	24	24	26	30			4.5J-13
	or 175/70SR13		•	24	24	26	30			5J-13
Astra Saloon (1979-83)	155SR13		•	25	25	28	32			5J-13
	or 175/70SR13		•	23	23	26	30			5.5J-13
Estate (1979-83)	155SR13		•	25	29	29	43			5J-13
Cavalier Saloon (1979-83)	165SR13		•	24	24	29	32	35	37	5J-13
	or 185/70SR13		•	23	23	26	26			5J-13
Coupe (1979-83)	185/70SR13		•	26	26	29	29			5.5J-13
SR (1983)	195/60HR14		•	28	28	32	34	35	37	5.5J-14
Carlton (1979-83)	175SR14		•	26	26	29	32	29	32	5.5J-14
	or 185/70SR14		•	26	26	29	32			5.5J-14
Royale (1979-83)	195/70HR14		•	32	32	36	41	36	41	6J-14
Viceroy (1981-83)	175HR14		•	29	29	32	38			6J-14
Volkswagen										
1200 Type1 Beetle (1979-80)	560-15		•	16	27	18	27			4.5J-15
	or 155SR15		•	18	27	18	27			4.5J-15
	or 185/70VR15		•	18	27	18	27			4.5J-15
Polo (1979-81)	135SR13		•	23	23	26	28			4.5J-13
	or 145SR13		•	21	21	24	27			4.5J-13
	or 155/70SR13		•	21	21	24	27			4.5J-13
Polo (1982-83)	135SR13		•	24	24	27	31			4.5J-13
	or 145SR13		•	23	23	24	30			4.5J-13
	or 155/70SR13		•	23	23	24	30			4.5J-13
Derby (1979-81)	145SR13		•	21	21	24	27			4.5J-13
	or 155/70SR13		•	21	21	24	27			4.5J-13
Derby (1982)	145SR13		•	23	23	24	30			4.5J-13
	or 155/70SR13		•	23	23	24	30			4.5J-13
Golf (1979-83)	145SR13		•	24	24	26	31			4.5J-13
	or 155SR13		•	24	24	26	31			4.5J-13
	or 175/70SR13		•	24	24	26	31			5.5J-13
GLi Convert (1983)	175/70HR13		•	26	26	26	31			5J-13
Jetta (1979-83)	155SR13		•	24	24	26	31			5J-13
	or **175/70SR13**		•	24	24	26	31			5.5J-13
Scirocco (1979-83)	155SR13		•	24	24	26	31			5J-13
	or 175/70SR13		•	24	24	26	31			5.5J-13
GTi; Storm (1983)	175/70HR13		•	26	26	27	31			6J-13
Passat Saloon (1979)	155SR13		•	24	24	26	31			5J-13
	or 175/70SR13		•	24	24	26	31			5J-13
Estate (1979-83)	155SR13		•	24	24	26	34			5J-13
	or 175/70SR13		•	24	24	26	34			5J-13
	or 185/70SR13		•	26	26	27	33			5.5J-13
	or 195/60HR14		•	26	26	27	33			6J-14
Santana (1983)	195/60HR14		•	27	27	28	33			6J-14
Volvo										
343; 345 (1979-83)	155SR13		•	27	30	27	34	27	34	5J-13
	or 175/70SR13		•	27	30	27	34	27	34	5.5J-13
244 (1979-83)	175SR14		•	26	27	26	32	31	36	5J-14
	or 185/70SR14		•	26	27	27	32	31	36	5.5J-14
244 GLT (1983)	195/60HR15		•	26	27	27	32			6J-15
245 (1979-83)	185SR14		•	27	27	28	34	31	37	5.5J-14
264 (1979-83)	175SR14		•	27	27	27	32	31	36	5J-14
	or 185/70HR14		•	27	27	28	34	31	37	5.5J-14
265 (1979-80)	185SR14		•	27	27	28	34	31	37	5.5J-14
265 (1981-83)	185SR14		•	27	30	28	40	28	40	5.5J-14
760GLE (1983)	195/60HR15		•	30	33	30	33			6J-15
Zastava										
Yugo 45 (1983)	145SR13		•	24	26	26	28			4.5J-13
45GL (1983)	155/70SR13		•	26	24	28	26			5J-13
Yugo 311; 511; 513 (1983)	145SR13		•	26	24	28	26			4.5J-13
Yugo 311GL; 513GL (1983)	165/70SR13		•	26	24	28	26			5J-13

Guide to Car Tyre Fitments

The following fitments are applicable to cars having single wheels on each axle and with front or with rear wheel drive.

Preferred Fitments Steel braced radial ply tyres on all four wheels. Textile braced radial ply tyres on all four wheels. Diagonal ply tyres on all four wheels.

Permissible Fitments Textile braced and steel braced radial ply tyres may be mixed in any combination. The best mixture is in axle pairs with textile braced radial ply tyres on the front axle and steel braced radial ply on the rear axle.

Diagonal ply tyres and radial ply (textile or steel braced) tyres may be mixed ONLY if the diagonal ply tyres are fitted to the front axle with radial ply tyres on the rear axle.

Illegal Fitments Diagonal tyres MUST NOT be fitted to the REAR axle with radial ply (textile or steel braced) tyres on the FRONT axle.

A diagonal ply tyre and a radial ply (steel or textile braced) tyre MUST NOT be fitted on the same axle.

Wheels Where radial ply tubeless tyres are to be fitted, always ensure that the wheels are suitable.

Tubes If the original tyres were fitted with tubes, new tubes should always be fitted in replacement tyres. Dunlop tubeless tyres may be fitted with a tube.

Important Note

Some high performance cars are extremely sensitive to tyre combinations. It is advisable to fit the same type and construction of tyres as were fitted when the car was new. IF IN DOUBT CONSULT DUNLOP LIMITED.